



For the Builders of a
Better World™

LATAPOXY® 300 ADHESIVE



PRODUCT DESCRIPTION

LATAPOXY® 300 ADHESIVE is a high-performance epoxy adhesive designed to ensure maximum strength and durability. It adheres securely to numerous surfaces, provided they are stable and clean. The adhesive is easy to apply and, when fresh, can be cleaned with water. **LATAPOXY® 300 ADHESIVE** is supplied in a three-component kit, consisting of: epoxy resin hardener and silica-based inert filler, resistant to chemical agents. This product is ideal for installation on walls and floors, both indoors and outdoors, in wet or dry areas, and even in areas subject to continuous immersion.

USES

- Laying of porcelain stoneware, thin ceramic slabs, non-absorbent single-fired tiles, double-fired tiles, natural and reconstituted stones that are stable in humidity, even large formats and glass mosaics.
- For the installation of large-format tiles.
- For indoor and outdoor installation of ceramic, porcelain, glass and stone tiles.
- Installation of green and white marble and moisture-sensitive agglomerates that tend to stain or deform when installed with traditional cementitious adhesives.
- For walls or floors.
- For laying on existing tiles.
- Laying of coverings subject to constant immersion, such as swimming pools or tanks.
- For rubber and wooden floors.
- For areas with heavy and intense traffic.

ADVANTAGES

- Adhesive for all types of applications — excellent for outdoor applications, swimming pools and stone.
- Available in white.
- Three-component — resin, hardener and aggregate.
- Highly deformable.
- Thixotropic and deformable — excellent workability.
- No vertical slippage — suitable for walls.
- High mechanical strength.
- Highly resistant to sagging.

SUITABLE SUBSTRATES

- Concrete.
- Tiles and stone.
- Wooden panels (indoor use only).
- Cement blocks.
- Vinyl adhesive residues.
- Vinyl tiles or other resilient tiles (indoor use only).
- Screed and cement mortar.
- Plasterboard (indoor use only, in dry environments).
- Cement plaster.
- Cement terrazzo flooring.
- Formica laminate (indoor use only).
- Cement board (consult the board manufacturer for installation advice and to verify suitability for outdoor use).
- Steel.
- Polystyrene panels.

PACKAGING

White – the kit includes:

- Part A (0.4 kg)
- Part B (0.8 kg)
- Part C powder (3.8 kg)

COVERAGE / CONSUMPTION

- 3.5 – 3.7 kg/m² with a 6x6 mm notched trowel.
- 4.3 – 4.0 kg/m² with 4x4 mm notched trowel.
- 4.5 – 4.4 kg/m² with 3x3 mm notched trowel.

TOOLS



LATICRETE Europe S.r.l. a socio unico | Via Paletti snc | 41051 Castelnovo Rangone (MO) | ITALIA | +39 059 535540 | www.laticrete.eu

Specifications may be subject to change without notice. Refer to the product datasheet for the most up-to-date information.
The results reported are indicative and reflect the test procedures used. Actual performance on site depends on installation methods and site conditions.
©2025 LATICRETE® International, Inc. All trademarks shown are the intellectual properties of their respective owners.



Discover
More